## **AR530 ARTICULATED CONTOUR ROTARY MOWER**





- TRUEDECK™ HEAVY-DUTY CONTOURING
- SUPERIOR AFTER-CUT APPEARANCE
- QUICK AND EASY DECK ADJUSTMENT
- · TRUSTWORTHY Kubola ENGINE

Redesigned from the ground up, the AR530 contour rotary mower is built to give you the best.

Designed with TRUEDECK™ heavy-duty contouring decks, with best in class clippings distribution and superior after-cut quality, it climbs hills and contours smoothly, eliminating the risk of scalping.

The AR530 offers quick and easy deck adjustments and a trustworthy Kubota® engine you can rely on.





SINCERELY

For information and support: www.jacobsen.com / +44 (0) 1473 270 000







## **AR530**

■ 692774 Blade 23.14 combo

■ 692775 Blade 23.14 mulch

■ 677080 Kit - quick release pin, 5 gang

■ 68127 Canopy kit







Vertical lift on outside decks for maneuverability



50.2 HP (37.4 kW) diesel Kubota® engine



 $\mathsf{TRUEDECK}^{\scriptscriptstyle\mathsf{IM}}\,\mathsf{heavy}\text{-}\mathsf{duty}\;\mathsf{cutting}\;\mathsf{decks}$ 

■ 698272 Roller - service 76 x 567 solid polymer

■ 10002064 Kit - 23" grooved roller scraper

■ 4394939 Acc, cargo net

■ 10013137 Kit - deck bumper 23"

DECKS & CUTTING UNITS	
NUMBER AND SIZE	5 x TRUEDECK™ 23" (58.4cm) rotary cutting units. Equipped for rear-discharge chute and smooth rear roller. Mulching baffle, non-striping rear roller and rear roller scrapers available
BLADE MATERIAL	$5 \times 22.4$ " (56.8cm) heat treated alloy combo blades
DECK LIFT & LOWER	Hand operated, joystick controlled hydraulic lift system
WEIGHT TRANSFER	Adjustable hydraulic weight transfer – automatic electronic activation at operator controls with mow switch. Selectable through control console
DECK CONSTRUCTION	10-gauge, heavy duty modular deck construction
TRACTION, BRAKES & SPEED	
TRACTION DRIVE	SureTrac II™ AWD, a unique parallel hydrostatic system, servo-controlled variable displacement hydro; four high-torque wheel motors; 2WD transport and reverse
DECK DRIVE	Fixed displacement, self-lubricating with 1" (2.54cm) diameter shaft; double sealed bearings
HYDRAULIC SYSTEM	10 gal. (37.9L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter, 40 gpm. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic through traction system
PARKING BRAKES	No-Maintenance, Integrated Wet Parking Brake
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	7mph (11.3km/h)
REVERSE SPEED	8.7mph (14km/h)
WEIGHTS & DIMENSIONS	
WEIGHT	3451lb. (1565kg) full fluids
LENGTH	137.5" (3.49m)
OVERALL HEIGHT (ROPS UP)	91.6" (232.6cm)
WHEELBASE	63" (1.6m)
TRANSPORT WIDTH	88.6" (2.25m)
WORKING WIDTH	95.3" (2.42m)
WARRANTY	
MOWER WARRANTY	2 Years
ACCESSORIES	

■ 677261 Kit - quick release pin, 7 gang

■ 686406 Kit - hood latch lock

■ 687204 Kit - ROPS bracket

■ 689563 Kit - 23" cable scraper