

AR530

ARTICULATED CONTOUR ROTARY MOWER

UNRIVALLED IN MANEUVERABILITY AND TRACTION

The AR530 is designed for operator convenience and the best execution. It features Jacobsen's TrueDeck™ heavy-duty contouring decks that provide excellent clipping distribution and eliminate the risk of scalping. Powered by a trustworthy Kubota® 50.2 HP diesel engine, it ensures efficient fuel consumption and the necessary power to handle various terrains. This mower ensures high-level traction with the SureTrac II™ AWD for challenging conditions, making it the machine to rely on.



**CUT UP TO 4.5 ACRES
PER HOUR**

**PROGRAMMABLE FREQUENCY
OF CLIP**

**QUICK AND EASY DECK
ADJUSTMENT**

CUT WIDTH

90"
(2.3M)

CUT HEIGHT

0.75" - 4.5"
(19MM - 114MM)
0.25" (6MM) INCREMENTS

FUEL CAPACITY

17 GAL
(64.2L)

MOWER ENGINE

**KUBOTA
50.2HP**
(37.4KW) DIESEL



JACOBSEN

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10024-G3 (Rev. 01/2025)

AR530

UNRIVALLED IN MANEUVERABILITY
AND TRACTION



A programmable and dynamic frequency of clip which reacts to an operator's skill, providing precise reel control.



The INTELeTRAC 3WD System continually monitors and adjusts the SLF1 to prevent scuffing, and limits wheel slip or spin.



Get a range of customization options with the SLF1 ELITE to suit whatever your turf needs. Easily switch between reel units and verticut units for a more versatile workday.



DECKS & CUTTING UNITS

NUMBER AND SIZE	5 x TRUEDECK™ 23" (58.4cm) rotary cutting units. Equipped for rear-discharge chute and smooth rear roller. Mulching baffle, non-stripping rear roller and rear roller scrapers available
BLADE MATERIAL	5 x 22.4" (56.8cm) heat treated alloy combo blades
DECK LIFT & LOWER	Hand operated, joystick controlled hydraulic lift system
WEIGHT TRANSFER	Adjustable hydraulic weight transfer – automatic electronic activation at operator controls with mow switch. Selectable through control console
DECK CONSTRUCTION	Heavy duty modular deck construction
TRACTION, BRAKES & SPEED	
TRACTION DRIVE	SureTrac II™ AWD, a unique parallel hydrostatic system, servo-controlled variable displacement hydro; four high-torque wheel motors; 2WD transport and reverse
DECK DRIVE	Fixed displacement, self-lubricating with 1" (2.54cm) diameter shaft; double sealed bearings
HYDRAULIC SYSTEM	10 gal. (37.9L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter, 40 gpm. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic through traction system
PARKING BRAKES	No-Maintenance, Integrated Wet Parking Brake
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	5.5mph (8.8kph)
TRANSPORT SPEED	9.3mph (15kph)

WEIGHTS & DIMENSIONS

WEIGHT	3451lb. (1565kg) full fluids
LENGTH	137.5" (3.49m)
OVERALL HEIGHT (ROPS UP)	91.6" (232.6cm)
WHEELBASE	63" (1.6m)
TRANSPORT	88.6" (2.25m)
WORKING WIDTH	95.3" (2.42m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- 692771 Blade 23.14 Hi-lift
- 692774 Blade 23.14 combo
- 692775 Blade 23.14 mulch
- 68127 Canopy kit
- 677080 Kit - quick release pin, 5 gang
- 677092 Kit - mulching, 23"
- 677261 Kit - quick release pin, 7 gang
- 689563 Kit - 23" cable scraper
- 698270 Roller - service 76 x 567 grooved polymer
- 698272 Roller - service 76 x 567 solid polymer
- 4394939 Acc, cargo net
- 10002064 Kit - 23" grooved roller scraper



For information and support:

www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

