

# LF570

HIGH PERFORMANCE RIDE-ON  
REEL MOWER

## UNMATCHED PRECISION USING JACOBSEN'S CUTTING-EDGE TECHNOLOGY

Meet all large turfcare needs with the LF570. This high performance reel mower features our SureTrac™ parallel-cross-series traction system for superior traction on hills and side slopes, and FlashAttach™ for quick and easy replacement of reel motors. Powered by a diesel Kubota® engine with either 37.5HP or 50.2HP, this machine can be trusted to tackle any job it's tasked with.



ADJUSTABLE HEIGHT OF CUT:  
0.375-1.125"

ONBOARD DIAGNOSTICS

SEMI-AUTOMATIC WET  
PARKING BRAKES

CUT WIDTH

**100"**  
(2.54M)

ERGONOMICS

PROGRAMMABLE  
**SPEED  
CONTROL**

CUTTING CAPACITY

UP TO **8** AC  
(3.24HA) / HR  
AT 8MPH (12.9KM/H)

CUTTING REELS

**5"** (12.7CM) OR  
**7"** (17.8CM)

MOWER ENGINE

**KUBOTA**  
**37.5**  
**/50.2HP**  
(28/37.4KW) DIESEL

TRANSPORT SPEED

**12MPH**  
(19.3KPH)



**JACOBSEN**

Actual operating power output may vary due to conditions of specific use.  
Run time will vary based on conditions of specific use, accessories, and terrain.  
NOTE: Specifications, while correct at time of printing, may change without notice.  
© 2025 Textron Specialized Vehicles Inc. 10038-G1 (Rev. 01/2025)

# LF570

## HIGH PERFORMANCE RIDE-ON REEL MOWER



The LF570 features a wet braking system integrated in the front wheel motors. These brakes eliminate the need for regular brake maintenance and extends the machine's lifespan.



Superior cutting capacity with up to 8 acres per hour at 8mph, ensure maximum productivity to get the job done.



Equipped with an impressive cutting width of 100-inches (2.54m), this machine is more than capable of mowing large areas efficiently.



### DECKS & CUTTING UNITS

NUMBER AND SIZE	9 or 11 heavy section fairway blades
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	Hand operated, joystick controlled hydraulic lift system, one-touch lift/lower control for all reel

### TRACTION, BRAKES & SPEED

TRACTION DRIVE	Variable displacement, electronically controlled hydrostatic drive; 4WD models: SureTrac™ parallel-cross-series traction system, four high-torque wheel motors, 2WD in reverse.
REEL DRIVE	Fixed displacement hydraulic motors with FlashAttach quick disconnect coupled reel motors. Standard on-board backlapping.
HYDRAULIC SYSTEM	114 gal. (53L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic braking through traction system
PARKING BRAKES	Semi-automatic, wet parking brakes integrated in front wheel motors
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	Up to 8mph (13kph) / T4I: Up to 11mph (19kph)
REVERSE SPEED	Selectable up to 5mph (8km/h)

### WEIGHTS & DIMENSIONS

	2WD	4WD
WEIGHT (excluding fuel)	3,221 lbs. (1,461 kg) 2WD High HP: 3,467 lbs. (1,573 kg)	3,552 lbs. (1,611 kg) 4WD High HP: 3,798 lbs. (1,723 kg) / T4I: 4WD: 2642 lbs. (1199kg)
LENGTH (less catchers)	108" (2.74m)	
OVERALL HEIGHT (ROPS up)	88" (2.23m)	
WHEELBASE	58" (1.5m)	
TRANSPORT WIDTH	87" (2.2m)	
WORKING WIDTH	115" (2.92m)	

### WARRANTY

MOWER WARRANTY	2 years
----------------	---------

### ACCESSORIES

- 55.9cm (22") Front rollers ranging from 5.1cm (2") to 7.6cm (3") - solid tube steel, grooved assembled or machined aluminum or steel
- Turf Groomer®
- Powered rear roller cleaning brush
- Canopy/Sunshade
- Grass Catcher
- High-cut kit
- Premium air suspension seat
- LED operator platform light kit
- Hood locking latch (required for CE)
- Verticut reels



For information and support:

[www.jacobsen.com](http://www.jacobsen.com) / +44 (0) 1473 270 000 / +1-888-438-3946

