

HR3 ELITE[®]

LITHIUM ELECTRIC OUTFRONT
MOWER

MOW ANYWHERE WITH UNLIMITED LITHIUM POTENTIAL

The HR3 ELITE is a game-changer in turf maintenance, delivering Jacobsen's industry-leading signature cut and unmatched operational efficiency. This machine will go anywhere the operator needs with the help of the proven, powerful ELiTE Lithium powertrain, activated by Samsung SDI Technology. Combine this with 80% lower running costs compared to internal combustion engines and experience an elite cutting experience. This versatile machine features a robust mowing deck design and a high comfort operator platform, ensuring efficient and comfortable use.



1.6-METER CUTTING CAPACITY

8 HOUR + RUN TIME

ZERO TAILPIPE EMISSIONS

TRANSPORT SPEED

25KPH
(15MPH)

CUT HEIGHT

1"- 4.5"
(25-115MM)

CUTTING CAPACITY

1.73 ha/hr
X 12 km/h
(4.27 ACRE/HR X 7.5 MPH)

RUN TIME

3
BLADE OUTFRONT

FUEL CAPACITY

**ZERO
FUEL**

POWERTRAIN

**ELiTE
LITHIUM**



JACOBSEN[®]

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10041-G1 (Rev. 01/2025)

HR3 ELITE[™]

LITHIUM ELECTRIC OUTFRONT MOWER



Road safe features, including LED road lights, mirrors, and an amber warning beacon, including high transport speeds of 25 kph (15mph) allowing for higher productivity without compromising operator safety.



This machine's ergonomic operator station has fingertip control, an adjustable armrest, and multiple storage options for a more pleasant working environment.



The high-strength steel construction and solid bumper rails ensure the deck can withstand heavy use and impacts, extending the overall lifespan of the mower.



DECKS & CUTTING UNITS

NUMBER AND SIZE	1 x 60" (1.52m) front deck; 2 x 44" (1.12m) wing units
BLADE MATERIAL	MARBAIN® boron alloy steel
DECK LIFT & LOWER	Individual via fingertip operated joysticks
WEIGHT TRANSFER	On demand electrically operated hydraulic weight transfer system
DECK CONSTRUCTION	11 gauge (3mm) Strenx, high strength steel shell

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Hydrostatic closed loop parallel-cross-series SureTrac™ system
DECK DRIVE	Seven individual hydraulic motors with self lubricating integral bearings
HYDRAULIC SYSTEM	13.3 gal. (50.2L) reservoir with 10 micron remote charge filters and suction screening at tank. Oil cooler in side by side radiator.
SERVICE BRAKES	Dynamic through hydrostatic traction system
PARKING BRAKES	Automatic wet parking brakes integrated into wheel motors
STEERING	Power Steering
MOWING SPEED	10mph (16.4km/h)
REVERSE SPEED	4mph (6.4km/h)

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	3873 lbs (1756kg) with ROPS, 4356 lbs. (1976kg) with cab
LENGTH (less catchers)	143" (3.62m) front deck down
OVERALL HEIGHT (ROPS up)	83" (2.1m)
WHEELBASE	64" (1.65m)
TRANSPORT WIDTH	65" (1.67m)
WORKING WIDTH	143" (3.63m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- Road light kit
- Canopy/sunshade
- Climate controlled cab
- Cab accessories - road light kit, Rear wiper kit



For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

