

LF550

HIGH PERFORMANCE RIDE-ON
REEL MOWER

REVOLUTIONIZING FAIRWAY MAINTENANCE

Conquer the toughest of fairways with the LF550. This machine has exceptional handling and control with reduced risk of slippage, including FlashAttach™ and AdaptiThrottle™ technologies that support seamless speed adjustments and reel motor changes for fluid operations. Experience unrivalled operator comfort with a tilt-adjustable steering wheel and a high-comfort suspension seat. The LF550 has an outstanding fuel capacity and superior traction, allowing you to work for longer regardless of the job.



EXCEPTIONAL HANDLING
AND CONTROL

100-INCH CUTTING WIDTH

FULL HYDRAULIC BRAKING
REDUCING WEAR AND TEAR

CUT WIDTH

100"
(2.54M)

ERGONOMICS

PROGRAMMABLE
**SPEED
CONTROL**

CUTTING CAPACITY

UP TO **8**^{AC}
(3.24HA) / HR
AT 8MPH (12.9KM/H)

CUTTING REELS

5X5" (12.7CM) OR
22" (55.9CM)

MOWER ENGINE

KUBOTA®
37.5
/50.2HP
(28/37.4KW) DIESEL

TRANSPORT SPEED

12^{MPH}
(19.3KPH)



JACOBSEN

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10039-G1 (Rev. 01/2025)

LF550

HIGH PERFORMANCE RIDE-ON REEL MOWER



The Jacobsen LF550's SureTrac™ 4WD system is engineered for superior handling and control on any terrain.



Offering fully adjustable mow speeds, the LF550 offers flexibility to tailor mowing pace to specific conditions.



Semi-automatic parking brakes temporarily apply the brakes when the machine stops, ensuring it remains securely in place until the operator drives away.



DECKS & CUTTING UNITS

NUMBER AND SIZE	9 or 11 heavy section fairway blades
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	Hand operated, joystick controlled hydraulic lift system, one-touch lift/lower control for all reel

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Variable displacement, electronically controlled hydrostatic drive; 4WD models: SureTrac™ parallel-cross-series traction system, four high-torque wheel motors, 2WD in reverse.
REEL DRIVE	Fixed displacement hydraulic motors with FlashAttach quick disconnect coupled reel motors. Standard on-board backlapping.
HYDRAULIC SYSTEM	14 gal. (53L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic braking through traction system
PARKING BRAKES	Semi-automatic, wet parking brakes integrated in front wheel motors
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	Selectable up to 11mph (19km/h)
REVERSE SPEED	Selectable up to 5mph (8km/h)

WEIGHTS & DIMENSIONS

	2WD	4WD
WEIGHT (excluding fuel)	2wd 3221lbs (1461kg) 2wd 37.5HP (28kW) 3467lbs (1573kg)	4wd 3552lbs (1611kg) 4wd 50.2HP (37.43kW) 3798lbs (1723kg)
LENGTH (less catchers)	108" (2.74m)	
OVERALL HEIGHT (ROPS up)	88" (2.23m)	
WHEELBASE	58" (1.5m)	
TRANSPORT WIDTH	87" (2.2m)	
WORKING WIDTH	115" (2.92m)	

WARRANTY

MOWER WARRANTY	2 years
----------------	---------

ACCESSORIES

- 55.9cm (22") Front rollers ranging from 5.1cm (2") to 7.6cm (3") - solid tube steel, grooved assembled or machined aluminum or steel
- Turf Groomer®
- Powered rear roller cleaning brush
- Canopy/Sunshade
- Grass Catcher
- High-cut kit
- Premium air suspension seat
- LED operator platform light kit
- Hood locking latch (required for CE)
- Verticut reels



For information and support:

www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

