

# AR331

## SIDE SHIFTING CONTOUR ROTARY MOWER

# ELEVATING TURF MAINTENANCE WITH ADVANCED TECHNOLOGY

This side-shifting contour rotary mower gives you power, strength, and precision at your command. The AR331 boasts enhanced maneuverability with Adaptishift™ Technology to cut around obstacles, and a trustworthy engine with 24.8 HP for consistent power. Easy and convenient deck adjustments make routine maintenance faster and user-friendly, giving you more time to spend on the turf.



REAR ROLLER FOR STRIPING

TRUEDECK™ HEAVY-DUTY  
CONTOURING CUTTING UNITS

ADAPTISHIFT™ SHIFTS  
CUTTING DECKS UP TO 30CM

### CUT WIDTH

**72"**

(182.22CM)

FEATURING ADAPTISHIFT WITH  
UP TO 12" (30.48CM) OF OFFSET

### CUT HEIGHT

**0.75"-**

**3.5"**

(19MM - 88MM)

### CUTTING CAPACITY

**4.5<sup>AC</sup>**

(1.83HA) / HR  
AT 6MPH (10KM/H)

### FUEL CAPACITY

**7.6<sup>GAL</sup>**

(28.7L)

### MOWER ENGINE

**24.8HP**

(18.6KW) DIESEL

### TRANSPORT SPEED

**8.7<sup>MPH</sup>**

(14KPH)



Actual operating power output may vary due to conditions of specific use.  
Run time will vary based on conditions of specific use, accessories, and terrain.  
NOTE: Specifications, while correct at time of printing, may change without notice.  
© 2025 Textron Specialized Vehicles Inc. 10023-G2 (Rev. 01/2025)

# AR331

## SIDE SHIFTING CONTOUR ROTARY MOWER



With 3WD, the power is distributed to three wheels, allowing it to maintain better stability, especially on steep slopes and wet grass.



Featuring intuitive on-board diagnostics, the AR331 allows the operator to continuously monitor its performance, alerting them of any potential problems in real time.



This machine offers executive operator comfort with an adjustable suspension seat, hydraulic power steering, and a tilt steering wheel.



### DECKS & CUTTING UNITS

NUMBER AND SIZE	3 x 27" (68.58cm) TrueDeck rotary cutting units
BLADE MATERIAL	Hardened, carbon steel alloy
DECK LIFT & LOWER	Armrest mounted joystick
WEIGHT TRANSFER	Adjustable hydraulic, electronically activated operator control
DECK CONSTRUCTION	9-gauge, stamped modular deck construction

### TRACTION, BRAKES & SPEED

TRACTION DRIVE	Parallel-series "on demand" 3WD
DECK DRIVE	Fixed displacement hydraulic
HYDRAULIC SYSTEM	8.7 gal. (33L) capacity, full flow filtration (10 micron filter); GreensCare biodegradable oil.
SERVICE BRAKES	Dynamic braking through hydrostatic drive
PARKING BRAKES	Service-free electronic wet disc
STEERING	Hydraulic power steering with tilt wheel
MOWING SPEED	6.2mph (10km/h)
TRANSPORT SPEED	3.7mph (6km/h)

### WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	2004lb (901kg)
LENGTH	122" (3.10m)
OVERALL HEIGHT (including ROPS)	82" (2.06m)
WHEELBASE	61" (1.54m)
TRANSPORT/WORKING WIDTH	77" (1.96m)

### WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

### ACCESSORIES

- Light kit
- Canopy
- Slick tires
- Mulching kit



For information and support:  
[www.jacobsen.com](http://www.jacobsen.com) / +44 (0) 1473 270 000 / +1-888-438-3946

